


Winkelstahl DIN EN 10 056 / DIN 1029



Winkelstahl
Größe 20/20 - 180/180

a	b	s	Querschnitt	Gewicht	a	b	s	Querschnitt	Gewicht
			cm ²	kg/m				cm ²	kg/m
30	20	3	1,42	1,11	90	60	8	11,40	8,96
30	20	4	1,85	1,45	100	50	6	8,73	6,85
40	20	3	1,72	1,35	100	50	10	14,10	11,10
40	20	4	2,25	1,77	100	65	7	11,20	8,77
45	30	3	2,19	1,72	100	65	9	14,20	11,10
45	30	5	3,53	2,77	100	75	7	11,90	9,32
50	30	5	3,78	2,96	100	75	9	15,10	11,80
50	40	4	3,46	2,71	120	80	8	15,50	12,20
50	40	5	4,27	3,35	120	80	10	19,10	15,00
60	30	5	4,29	3,37	130	65	8	15,10	11,90
60	30	7	5,85	4,59	130	65	10	18,60	14,60
60	40	5	4,79	3,76	130	75	8	15,90	12,50
60	40	7	6,55	5,14	130	75	10	19,60	15,40
65	50	5	5,54	4,35	130	90	10	21,20	16,60
65	50	9	9,58	7,52	150	75	9	19,50	15,30
75	50	5	6,04	4,74	150	75	11	23,60	18,60
75	50	9	10,50	8,23	150	90	10	23,20	18,20
75	55	5	6,30	4,95	150	100	10	24,20	19,00
75	55	9	10,90	8,59	150	100	12	28,70	22,60
80	40	6	6,89	5,41	160	80	10	23,20	18,20
80	40	8	9,01	7,07	160	80	12	27,50	21,60
80	65	6	8,41	6,60	180	90	10	26,20	20,60
80	65	10	13,60	10,70	200	100	10	29,20	23,00
90	60	6	8,69	6,82	200	100	12	34,80	27,30